

Poles, Inc.

Wood Pole Maintenance Solutions[®]

Copper Naphthenate Concentrate

Ground Contact Wood Preservative

8% Active Ingredient, 68% Copper Naphthenate, 8% Copper as Metal

* 8X Concentration vs. Retail Copper Naphthenate

* Industrial Grade

* Meets AWPA M 4-11 and P 36-11

* Dilute with Diesel or Mineral Spirits

* 24-Hour Dip

* Brush-on



Application Method	Concentrate Dilution w/Diesel	Concentrate Dilution w/Mineral Spirits	Solution as Metal (% Cu as Metal)	Solution % (Copper Naphthenate by Volume)	*Treated Wood Service Area
Brush 1 Coat	3.5 Gallons of Diesel to 1 Gallon of Concentrate	4 Gallons of Mineral Spirits to 1 Gallon of Concentrate	2%	17% to 19%	Above Ground
Brush Multiple Coats	3.5 Gallons of Diesel to 1 Gallon of Concentrate	4 Gallons of Mineral Spirits to 1 Gallon of Concentrate	2%	17% to 19%	Above Ground *Ground Contact
Dip 24-Hour	8 Gallons of Diesel to 1 Gallon of Concentrate	9 Gallons of Mineral Spirits to 1 Gallon of Concentrate	1%	8% to 10%	Above Ground **Ground Contact

*Additional coats of brushed on material will produce longer lasting results

** 24-hour dip treatments can produce long lasting ground contact results

For Use on Many Types of Wood, such as:

Fence Posts, Landscape Timbers, Bridges, Ammo Boxes

Available Packaging: 1 Gallon Jug, 5 Gallon Pail, 6x1 Case, 55 Gallon Drum, and 260 Gallon Tote

Orders & Information

719-685-0333

www.poles.com