

**Copper Naphthenate Concentrate, 8% as metal, 68% by Volume  
Dilution Rates and Service Area**

<b>Application Method</b>	<b>Concentrate Dilution w/Diesel</b>	<b>Concentrate Dilution w/Mineral Spirits</b>	<b>Solution as Metal (% Cu as Metal)</b>	<b>Solution % (Copper Naphthenate by Volume)</b>	<b>*Treated Wood Service area</b>
<b>Brush On 1 Coat</b>	3.5 Gallons of Diesel to 1 Gallon of Concentrate	4 Gallons of Mineral Spirits to 1 Gallon of Concentrate	2%	17% to 19%	Above Ground
<b>Brush On Multiple Coats</b>	3.5 Gallons of Diesel to 1 Gallon of Concentrate	4 Gallons of Mineral Spirits to 1 Gallon of Concentrate	2%	17% to 19%	Above Ground *Ground Contact
<b>Dip Treatment 24 Hour</b>	8 Gallons of Diesel to 1 Gallon of Concentrate	9 Gallons of Mineral Spirits to 1 Gallon of Concentrate	1%	8% to 10%	Above Ground Ground Contact

\*Copper Naphthenate is an EPA registered ground contact wood preservative; application must result in enough preservative to protect the wood.

**Contact:**  
**Randy S. Gross, 719-685-0444**  
**Fax 719-685-3444**  
**Email: [randy@poles.com](mailto:randy@poles.com)**  
**Website: [www.poles.com](http://www.poles.com)**